

In the Specification

Page, 14, change the following paragraph to read as follows:

--[0037] Figure 2 is a perspective view of an exemplary embodiment ~~of an exemplary embodiment~~ of the present invention.--

Cancel pages 17-20.

Page 22, change the following paragraph to read as follows:

--[0053] A second end cap 50 seals the tube second end 34. A swivel loop 52 is attached to the second end cap and a clip hook 54 is attached to the swivel loop. A loop 56 is attached to the tube proximate the second end, through which a fastener strap 58 is threaded. The fastener strap has a first hook-and-loop portion end 60 and a second hook-and-loop portion end 62 for joining the strap 58 ~~[[44]]~~ about various objects.--

Pages 22-23, change the following paragraph to read as follows:

--[0055] The control assembly 76 is attached to the elongated member and adapted for receiving electric power from the portable electric power source, in this embodiment, a battery 78, as shown in Figure 6. As shown in Figure 3, the control assembly also includes ~~a flasher unit 80~~, a switch 82 for turning the lights 72 on and off, and a flasher unit control button 84 for a flasher unit. Using conventional technology, the control assembly provides light control functions including steady on, fast flash, slow flash, sequential lighting, and twinkle.--

Page 24, change the following paragraph to read as follows:

--[0059] Turning now to Figure 9, an exemplary embodiment of the device 20 is illustrated wherein the user 21 has placed a pair of the devices 20 along her upper torso 23 in suspender fashion, with the clip hooks 40 and similar hooks on the opposite side of user (not shown) ~~40,54~~ being attached to the user's belt.--